



AkzoNobel

# Material Safety Data Sheet

Date of printing : 6/22/2011.

Date of issue : 6/22/2011

## 1. Product and company identification

Prepared for  
ATTN:  
Chemcraft  
1431 Progress Ave.  
  
High Point, NC 27260 US

Prepared by  
Akzo Nobel Coatings Inc.  
1431 Progress Ave.  
High Point, NC 27261 US  
  
(336)841-5111  
In case of emergency (Health or Spills):  
CHEMTREC (US and Canada) (800) 424-9300

Product no. : 827-9014MCA  
Product - Class : UV Tinter Blue  
Customer Part Number :  
Customer ShipTo ID : 0000109024

## 2. Hazards identification

- Physical state** : Liquid.
- OSHA/HCS status** : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
- Emergency overview** : WARNING!  
COMBUSTIBLE LIQUID AND VAPOR. CAUSES SEVERE EYE IRRITATION. HARMFUL IF ABSORBED THROUGH SKIN OR IF SWALLOWED. CAUSES RESPIRATORY TRACT AND SKIN IRRITATION. CONTAINS MATERIAL THAT MAY CAUSE TARGET ORGAN DAMAGE, BASED ON ANIMAL DATA.  
Keep away from heat, sparks and flame. Do not breathe vapor or mist. Do not ingest. Do not get in eyes or on skin or clothing. Use only with adequate ventilation. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling.
- Routes of entry** : Dermal contact. Eye contact. Inhalation. Ingestion.
- Potential acute health effects**
- Inhalation** : Irritating to respiratory system.  
Other effects of inhalation may include: cough, headache, liver damage, nausea, shortness of breath, vomiting, wheezing,
- Ingestion** : Harmful if swallowed.  
Other effects of ingestion may include : abdominal pain, CNS effects, kidney damage, liver damage, nausea, poisoning, vomiting,
- Skin** : Toxic in contact with skin. Irritating to skin.  
Other effects of skin contact may include: dehydration, sensitization, Effects due to absorption through skin may include: CNS effects, kidney damage, nausea, vomiting, weakness,
- Eyes** : Severely irritating to eyes. Risk of serious damage to eyes.  
Other effects of eye contact may include : eye damage, opaqueness of cornea, redness,

## 2. Hazards identification

### Potential chronic health effects

- Carcinogenicity** : No known significant effects or critical hazards.
- Mutagenicity** : No known significant effects or critical hazards.
- Teratogenicity** : No known significant effects or critical hazards.
- Target organs** : Contains material which may cause damage to the following organs: blood, kidneys, lungs, the reproductive system, liver, skin.

**Medical conditions aggravated by over-exposure** : Not available.

See toxicological information (Section 11)

## 3. Composition/information on ingredients

| <u>Name</u>                  | <u>CAS number</u> | <u>% by weight</u> | <u>Vapor pressure</u> | <u>Exposure limits</u>  |
|------------------------------|-------------------|--------------------|-----------------------|---|
| proprietary                  | -                 |                    | Not available.        |   |
| proprietary                  | -                 |                    | Not available.        |   |
| proprietary                  | -                 |                    | Not available.        |   |
| vinyl pyrrolidone            | 88-12-0           |                    | Not available.        | <b>ACGIH TLV (United States).</b><br>TWA: 0.05 ppm 8 hour(s).   |
| proprietary                  | -                 |                    | Not available.        | <b>ACGIH TLV (United States).</b><br>TWA: 1 mg/m <sup>3</sup> 8 hour(s).<br><b>OSHA PEL (United States).</b><br>TWA: 1 mg/m <sup>3</sup> 8 hour(s). |
| hydroxymethylphenylpropanone | 7473-98-5         |                    | Not available.        |   |
| talc                         | 14807-96-6        |                    | Not available.        | <b>ACGIH TLV (United States).</b><br>TWA: 2 mg/m <sup>3</sup> 8 hour(s).<br><b>OSHA PEL (United States).</b><br>TWA: 2 mg/m <sup>3</sup> 8 hour(s). |
| ethylene glycol diacrylate   | 2274-11-5         |                    | Not available.        |   |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

## 4. First aid measures

- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.
- Eye contact** : Get medical attention immediately if symptoms occur. Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids.
- Skin contact** : Get medical attention immediately if symptoms occur. In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Inhalation** : Get medical attention immediately if symptoms occur. Move exposed person to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen tight clothing such as a collar, tie, belt or waistband.
- Ingestion** : Get medical attention immediately. Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person.

## 5. Fire-fighting measures

- Flammability of the product** : Combustible liquid. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.
- Flash point** : Closed cup: >93.3°C (>200.0°F)
- Flammable limits** : Not available.
- Extinguishing media**
- Suitable** : Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.
- Not suitable** : Do not use water jet.
- Special exposure hazards** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
- Hazardous thermal decomposition products** : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide  
nitrogen oxides  
phosphorus oxides  
metal oxide/oxides
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.  
  
UNUSUAL FIRE HAZARDS: During emergency conditions, overexposure to products of combustion may cause a health hazard; symptoms may not be immediately apparent. Obtain medical attention.
- Special remarks on fire hazards** : Not available.
- Special remarks on explosion hazards** : Not available.

## 6. Accidental release measures

- Personal precautions** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.
- Methods for cleaning up**
- Small spill** : Stop leak if without risk. Move containers from spill area. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product.

## 7. Handling and storage

- Handling** : Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Do not enter confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Storage** : Store in accordance with local regulations. Store in approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

## 8. Exposure controls/personal protection

- Engineering measures** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits.
- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Personal protection** Selection of personal protective equipment (PPE) is to be established by the employer performing a PPE hazard assessment. In the U.S.A, OSHA requires completion of a documented PPE hazard assessment as described in 29 CFR 1910.132.
- Respiratory** : Use properly fitted respiratory protection complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.  
Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet sanding/flattening should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.
- Hands** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
- Eyes** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts.
- Skin** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Other protection** : Not available.

## 8. Exposure controls/personal protection

## 9. Physical and chemical properties

|                                   |                                    |
|-----------------------------------|------------------------------------|
| <b>Physical state</b>             | : Liquid.                          |
| <b>Burning time</b>               | : Not applicable.                  |
| <b>Burning rate</b>               | : Not applicable.                  |
| <b>Color</b>                      | : Not available.                   |
| <b>Odor</b>                       | : Not available.                   |
| <b>Taste</b>                      | : Not available.                   |
| <b>Molecular weight</b>           | : Not applicable.                  |
| <b>Molecular formula</b>          | : Not applicable.                  |
| <b>pH</b>                         | : Not available.                   |
| <b>Boiling/condensation point</b> | : 96.11 to 258.89°C (205 to 498°F) |
| <b>Melting/freezing point</b>     | : Not available.                   |
| <b>Critical temperature</b>       | : Not available.                   |
| <b>Relative density</b>           | : 1.128                            |
| <b>Vapor density</b>              | : Heavier than air                 |
| <b>Volatility</b>                 | : 0.03% (w/w)                      |
| <b>Odor threshold</b>             | : Not available.                   |
| <b>Evaporation rate</b>           | : Not available.                   |
| <b>Viscosity</b>                  | : Not available.                   |
| <b>Ionicity (in water)</b>        | : Not available.                   |
| <b>Dispersibility properties</b>  | : Not available.                   |
| <b>Solubility</b>                 | : Not available.                   |

## 10. Stability and reactivity

|   |   |
|---|---|
| <b>Chemical stability</b>                 | : The product is stable, under normal conditions of storage and use.  |
| <b>Hazardous polymerization</b>           | : Yes.  |
| <b>Conditions to avoid</b>                | : Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.<br>Other Conditions to avoid: light, storage under inert atmosphere, loss of dissolved air, avoid x-rays or uv radiation, loss polymerization inhibitors, |
| <b>Materials to avoid</b>                 | : Reactive or incompatible with the following materials: oxidizing materials, reducing materials, metals, acids and alkalis.  |
| <b>Hazardous decomposition products</b>   | : Not available.  |
| <b>Possibility of hazardous reactions</b> | : Under normal conditions of storage and use, hazardous reactions will not occur.   |

## 11. Toxicological information

### Acute toxicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|-------------------------|--------|---------|------|----------|
|-------------------------|--------|---------|------|----------|

## 11. Toxicological information

|                              |                 |        |                        |         |
|------------------------------|-----------------|--------|------------------------|---------|
| hydroxymethylphenylpropanone | LD50 Dermal     | Rat    | 6929 mg/kg             | -       |
|                              | LD50 Oral       | Rat    | 1694 mg/kg             | -       |
| vinyl pyrrolidone            | LD50 Dermal     | Rabbit | 560 mg/kg              | -       |
|                              | LD50 Oral       | Rat    | 1470 mg/kg             | -       |
|                              | LC50 Inhalation | Rat    | 3200 mg/m <sup>3</sup> | 4 hours |
|                              | Vapor           |        |                        |         |
| ethylene glycol diacrylate   | LD50 Dermal     | Rabbit | 621 mg/kg              | -       |
|                              | LD50 Oral       | Rat    | 300 mg/kg              | -       |
|                              | LC50 Inhalation | Mouse  | 350 mg/m <sup>3</sup>  | 4 hours |
|                              | Vapor           |        |                        |         |

### Carcinogenicity

Not available.

### Mutagenicity

Product/ingredient name

Test

Experiment

Result

Not available.

### Teratogenicity

Product/ingredient name

Result

Species

Dose

Exposure

Not available.

## 12. Ecological information

Data available upon request.

## 13. Disposal considerations

### Waste disposal

: The generation of waste should be avoided or minimized wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

## 14. Transport information

Note: Information contained in this section may vary from the actual shipping description depending on quantity in containers, mode of shipment and use of exemptions.

| Regulatory information | UN number      | Proper shipping name | Classes | PG* | Label | Additional information |
|------------------------|----------------|----------------------|---------|-----|-------|------------------------|
| DOT Classification     | Not regulated. | -                    | -       | -   |       |                        |
| TDG Classification     | Not regulated. | -                    | -       | -   |       | -                      |
| IMDG Class             | Not regulated. | -                    | -       | -   |       | -                      |
| IATA-DGR Class         | Not regulated. | -                    | -       | -   |       | -                      |

## 14. Transport information

PG\* : Packing group

## 15. Regulatory information

### United States

**U.S. Federal regulations** : **United States inventory (TSCA 8b)** : All components are listed or exempted.  
(HAPS) **Clean Air Act (CAA) 112 regulated toxic substances:** toluene

### SARA 313

|  | <u>Product name</u> | <u>CAS number</u> | <u>Concentration</u> |
|--|---------------------|-------------------|----------------------|
| <b>Form R - Reporting requirements</b> | : Not applicable.   |                   |                      |

SARA 313 notifications must not be detached from the MSDS and any copying and redistribution of the MSDS shall include copying and redistribution of the notice attached to copies of the MSDS subsequently redistributed.

### California Prop. 65

**WARNING:** This product contains less than 1% of a chemical known to the State of California to cause birth defects or other reproductive harm.

| <u>Ingredient name</u> | <u>Cancer</u> | <u>Reproductive</u> | <u>No significant risk level</u> | <u>Maximum acceptable dosage level</u> |
|------------------------|---------------|---------------------|----------------------------------|--|
| toluene                | No.           | Yes.                | No.                              | No.                                    |

### Canada

**Canada inventory** : All components of this product are on the CEPA DSL inventory.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

### International regulations

**International lists** : **Australia inventory (AICS):** Not determined.  
**China inventory (IECSC):** Not determined.  
**Japan inventory:** Not determined.  
**Korea inventory:** Not determined.  
**New Zealand Inventory of Chemicals (NZIoC):** Not determined.  
**Philippines inventory (PICCS):** Not determined.

\*\* All values in this section reported as percentage by weight, unless otherwise specified.

## 16. Other information

**HMIS III ® Hazardous Material Information System (U.S.A.)** :

|                     |   |   |
|---------------------|---|---|
| Health              | * | 2 |
| Flammability        |   | 1 |
| Physical hazards    |   | 2 |
| Personal protection |   |   |

Caution: HMIS III ® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risk, and 4 representing severe hazards or risk. Although HMIS III ® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS III ® ratings are to be used with a fully implemented HMIS III ® program. HMIS III ® is a registered mark of the National Paint & Coatings Association (NPCA).

The customer is responsible for determining the PPE code for this material.

**Other special considerations** : Not available.

Notice to reader

## 16. Other information

**IMPORTANT NOTE** The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Brand names mentioned in this data sheet are trademarks of or are licensed to Akzo Nobel.