

# Franklin International

## Material Safety Data Sheet

Product name : Titebond Instant Bond Activator

### 1. Product and company identification

**CAS #** : mixture  
**Address** : Franklin International  
2020 Bruck Street  
Columbus OH 43207  
**Contact person** : Franklin Technical Services  
**Telephone** : (800) 877-4583  
**Emergency phone:** : Franklin Security  
(614) 445-1300  
**Reference number** : 00  
**Product code** : 6311  
**Date of revision** : 4/29/2009.  
**Print date** : 1/27/2010.  
**Chemtrec (24 Hour)** : (800) 424 - 9300  
**Chemtrec International** : (703) 527 - 3887  
**Product use** : activator  
**Product type** : solvent based

### 2. Hazards identification

**Physical state** : Liquid.  
**Odor** : Hydrocarbon. [Strong]  
**OSHA/HCS status** : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).  
**Emergency overview** : DANGER!  
EXTREMELY FLAMMABLE LIQUID AND VAPOR. FLAMMABLE. VAPOR MAY CAUSE FLASH FIRE. CAUSES EYE AND SKIN IRRITATION. MAY BE HARMFUL IF SWALLOWED. MAY CAUSE RESPIRATORY TRACT IRRITATION. PROLONGED OR REPEATED CONTACT MAY DRY SKIN AND CAUSE IRRITATION. CONTAINS MATERIAL THAT MAY CAUSE TARGET ORGAN DAMAGE.  
Extremely flammable liquid. May be harmful if swallowed. Severely irritating to eyes. Irritating to skin. Moderately irritating to the respiratory system. Defatting to the skin. Keep away from heat, sparks and flame. Do not breathe vapor or mist. Do not ingest. Do not get in eyes. Avoid contact with skin and clothing. Contains material that may cause target organ damage. Use only with adequate ventilation. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling.  
**Routes of entry** : Dermal contact. Eye contact. Inhalation. Ingestion.  
**Potential acute health effects**  
**Inhalation** : Moderately irritating to the respiratory system.  
**Ingestion** : Harmful if swallowed.  
**Skin** : Irritating to skin. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.  
**Eyes** : Severely irritating to eyes. Risk of serious damage to eyes. This product may irritate eyes upon contact.

## 2. Hazards identification

### Potential chronic health effects

- Chronic effects** : Contains material that may cause target organ damage. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.
- Carcinogenicity** : No known significant effects or critical hazards.
- Mutagenicity** : No known significant effects or critical hazards.
- Teratogenicity** : No known significant effects or critical hazards.
- Developmental effects** : No known significant effects or critical hazards.
- Fertility effects** : No known significant effects or critical hazards.
- Target organs** : Contains material which may cause damage to the following organs: kidneys, liver, upper respiratory tract, skin, central nervous system (CNS), eye, lens or cornea.

### Over-exposure signs/symptoms

- Inhalation** : High vapor concentrations can cause headaches, dizziness, drowsiness and nausea and may lead to unconsciousness. Adverse symptoms may include the following:  
respiratory tract irritation  
coughing
- Ingestion** : No specific data.
- Skin** : Adverse symptoms may include the following:  
irritation  
redness  
dryness  
cracking
- Eyes** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness
- Medical conditions aggravated by over-exposure** : Pre-existing disorders involving any target organs mentioned in this MSDS as being at risk may be aggravated by over-exposure to this product.

See toxicological information (section 11)

## 3. Composition/information on ingredients

### United States

Name	CAS number	%
naphtha	8030-30-6	75 - 100
heptane	142-82-5	10 - 25
methylcyclohexane	108-87-2	1 - 5

### Canada

Name	CAS number	%
naphtha	8030-30-6	75 - 100
heptane	142-82-5	10 - 25
methylcyclohexane	108-87-2	1 - 5

### Mexico

Name	CAS number	UN number	%	IDLH	Classification			
					H	F	R	Special
naphtha	8030-30-6	UN1993	75 - 100	1000 ppm	0	2	0	
heptane	142-82-5	UN1993	10 - 25	750 ppm	0	3	0	
methylcyclohexane	108-87-2	UN1993	1 - 5	1200 ppm	0	3	0	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

## 4 . First aid measures

- Eye contact** : Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention immediately.
- Skin contact** : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention immediately.
- Inhalation** : Move exposed person to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention immediately.
- Ingestion** : Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.
- Notes to physician** : No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

## 5 . Fire-fighting measures

- Flammability of the product** : Extremely flammable liquid. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard.
- Extinguishing media**
- Suitable** : Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.
- Not suitable** : Do not use water jet.
- Special exposure hazards** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## 6 . Accidental release measures

- Personal precautions** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see section 8).
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. Absorb with an inert material.
- Large spill** : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 for emergency contact information and section 13 for waste disposal.

## 7. Handling and storage

- Handling** : Put on appropriate personal protective equipment (see section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material.
- Storage** : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

## 8. Exposure controls/personal protection

### United States

Ingredient	Exposure limits
naphtha	<p><b>ACGIH TLV (United States, 1/2008).</b>                      TWA: 400 ppm 8 hour(s).                      TWA: 1590 mg/m<sup>3</sup> 8 hour(s).</p> <p><b>OSHA PEL 1989 (United States, 3/1989).</b>                      TWA: 100 ppm 8 hour(s).                      TWA: 400 mg/m<sup>3</sup> 8 hour(s).</p> <p><b>NIOSH REL (United States, 6/2008).</b>                      TWA: 100 ppm 10 hour(s).                      TWA: 400 mg/m<sup>3</sup> 10 hour(s).</p> <p><b>OSHA PEL (United States, 11/2006).</b>                      TWA: 100 ppm 8 hour(s).                      TWA: 400 mg/m<sup>3</sup> 8 hour(s).</p>
heptane	<p><b>ACGIH TLV (United States, 1/2008).</b>                      TWA: 400 ppm 8 hour(s).                      TWA: 1640 mg/m<sup>3</sup> 8 hour(s).                      STEL: 500 ppm 15 minute(s).                      STEL: 2050 mg/m<sup>3</sup> 15 minute(s).</p> <p><b>OSHA PEL 1989 (United States, 3/1989).</b>                      TWA: 400 ppm 8 hour(s).                      TWA: 1600 mg/m<sup>3</sup> 8 hour(s).                      STEL: 500 ppm 15 minute(s).                      STEL: 2000 mg/m<sup>3</sup> 15 minute(s).</p> <p><b>NIOSH REL (United States, 6/2008).</b>                      TWA: 85 ppm 10 hour(s).                      TWA: 350 mg/m<sup>3</sup> 10 hour(s).                      CEIL: 440 ppm 15 minute(s).                      CEIL: 1800 mg/m<sup>3</sup> 15 minute(s).</p> <p><b>OSHA PEL (United States, 11/2006).</b>                      TWA: 500 ppm 8 hour(s).                      TWA: 2000 mg/m<sup>3</sup> 8 hour(s).</p>
methylcyclohexane	<p><b>ACGIH TLV (United States, 1/2008).</b>                      TWA: 400 ppm 8 hour(s).</p>

## 8 . Exposure controls/personal protection

TWA: 1610 mg/m<sup>3</sup> 8 hour(s).  
**OSHA PEL 1989 (United States, 3/1989).**  
 TWA: 400 ppm 8 hour(s).  
 TWA: 1600 mg/m<sup>3</sup> 8 hour(s).  
**NIOSH REL (United States, 6/2008).**  
 TWA: 400 ppm 10 hour(s).  
 TWA: 1600 mg/m<sup>3</sup> 10 hour(s).  
**OSHA PEL (United States, 11/2006).**  
 TWA: 500 ppm 8 hour(s).  
 TWA: 2000 mg/m<sup>3</sup> 8 hour(s).

### Canada

Occupational exposure limits		TWA (8 hours)			STEL (15 mins)			Ceiling			
Ingredient	List name	ppm	mg/m <sup>3</sup>	Other	ppm	mg/m <sup>3</sup>	Other	ppm	mg/m <sup>3</sup>	Other	Notations
naphtha	US ACGIH 1/2008	400	1590	-	-	-	-	-	-	-	
	AB 6/2008	400	1590	-	-	-	-	-	-	-	
	BC 6/2008	400	-	-	-	-	-	-	-	-	
	ON 6/2008	-	1350	-	-	-	-	-	-	-	
	QC 6/2008	400	1590	-	-	-	-	-	-	-	
heptane	US ACGIH 1/2008	400	1640	-	500	2050	-	-	-	-	
	AB 6/2008	400	1640	-	500	2050	-	-	-	-	
	BC 6/2008	400	-	-	500	-	-	-	-	-	
	ON 6/2008	400	1635	-	500	2045	-	-	-	-	
	QC 6/2008	400	1640	-	500	2050	-	-	-	-	
methylcyclohexane	US ACGIH 1/2008	400	1610	-	-	-	-	-	-	-	
	AB 6/2008	400	1610	-	-	-	-	-	-	-	
	BC 6/2008	400	-	-	-	-	-	-	-	-	
	ON 6/2008	400	1600	-	-	-	-	-	-	-	
	QC 6/2008	400	1610	-	-	-	-	-	-	-	

### Mexico

Ingredient	Exposure limits
naphtha	<b>NOM-010-STPS (Mexico, 9/2000).</b> LMPE-PPT: 400 ppm 8 hour(s). LMPE-PPT: 1600 mg/m <sup>3</sup> 8 hour(s).
heptane	<b>NOM-010-STPS (Mexico, 9/2000). Absorbed through skin.</b> LMPE-PPT: 400 ppm 8 hour(s). LMPE-PPT: 1600 mg/m <sup>3</sup> 8 hour(s). LMPE-CT: 2000 mg/m <sup>3</sup> 15 minute(s). LMPE-CT: 500 ppm 15 minute(s).
methylcyclohexane	<b>NOM-010-STPS (Mexico, 9/2000).</b> LMPE-PPT: 400 ppm 8 hour(s). LMPE-PPT: 1600 mg/m <sup>3</sup> 8 hour(s). LMPE-CT: 2000 mg/m <sup>3</sup> 15 minute(s). LMPE-CT: 500 ppm 15 minute(s).

Consult local authorities for acceptable exposure limits.

**Recommended monitoring procedures** : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.

**Engineering measures** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

## 8 . Exposure controls/personal protection

- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Personal protection**
- Respiratory** : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
- Hands** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
- Eyes** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts.
- Skin** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

## 9 . Physical and chemical properties

- Physical state** : Liquid.
- Flash point** : Closed cup: -9.4444°C (15°F) [Setaflash.]
- Flammable limits** : Lower: 1.1%  
Upper: 6.7%
- Color** : Clear.
- Odor** : Hydrocarbon. [Strong]
- Boiling/condensation point** : >90.556°C (>195°F)
- Relative density** : 0.79
- Volatility** : 100% (w/w)
- VOC (less water, less exempt solvents)** : 720 g/l
- Solubility** : Insoluble in the following materials: cold water and hot water.

## 10 . Stability and reactivity

- Chemical stability** : The product is stable.
- Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.
- Hazardous polymerization** : Under normal conditions of storage and use, hazardous polymerization will not occur.
- Conditions to avoid** : Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
- Materials to avoid** : Highly reactive or incompatible with the following materials:  
oxidizing materials
- Incompatibility** : Reactive or incompatible with the following materials: oxidizing materials and combustible materials.
- Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.
- Conditions of reactivity** : Highly flammable in the presence of the following materials or conditions: open flames, sparks and static discharge.

## 11 . Toxicological information

### United States

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
naphtha	LD50 Dermal	Rabbit	>3 gm/kg	-
	LD50 Oral	Rat	>5 gm/kg	-
heptane	LC50 Inhalation	Rat	103 gm/m3	4 hours
methylcyclohexane	LD Dermal	Rabbit	>86700 mg/kg	-
	LD50 Oral	Rat	>3200 mg/kg	-

#### Chronic toxicity

No known significant effects or critical hazards.

#### Irritation/Corrosion

No known significant effects or critical hazards.

#### Sensitizer

No known significant effects or critical hazards.

#### Carcinogenicity

No known significant effects or critical hazards.

#### Mutagenicity

No known significant effects or critical hazards.

#### Teratogenicity

No known significant effects or critical hazards.

#### Reproductive toxicity

No known significant effects or critical hazards.

### Canada

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
naphtha	LD50 Dermal	Rabbit	>3 gm/kg	-
	LD50 Oral	Rat	>5 gm/kg	-
heptane	LC50 Inhalation	Rat	103 gm/m3	4 hours
methylcyclohexane	LD Dermal	Rabbit	>86700 mg/kg	-
	LD50 Oral	Rat	>3200 mg/kg	-

#### Chronic toxicity

No known significant effects or critical hazards.

#### Irritation/Corrosion

No known significant effects or critical hazards.

#### Sensitizer

No known significant effects or critical hazards.

#### Carcinogenicity

No known significant effects or critical hazards.

#### Mutagenicity

No known significant effects or critical hazards.

#### Teratogenicity

No known significant effects or critical hazards.

#### Reproductive toxicity

No known significant effects or critical hazards.

### Mexico

#### Acute toxicity

## 11 . Toxicological information

Product/ingredient name	Result	Species	Dose	Exposure
naphtha	LD50 Dermal	Rabbit	>3 gm/kg	-
	LD50 Oral	Rat	>5 gm/kg	-
heptane	LC50 Inhalation	Rat	103 gm/m3	4 hours
methylcyclohexane	LD Dermal	Rabbit	>86700 mg/kg	-
	LD50 Oral	Rat	>3200 mg/kg	-

### Chronic toxicity

No known significant effects or critical hazards.

### Irritation/Corrosion

No known significant effects or critical hazards.

### Sensitizer

No known significant effects or critical hazards.

### Carcinogenicity

No known significant effects or critical hazards.

### Mutagenicity

No known significant effects or critical hazards.

### Teratogenicity

No known significant effects or critical hazards.

### Reproductive toxicity

No known significant effects or critical hazards.

## 12 . Ecological information

**Environmental effects** : No known significant effects or critical hazards.

### United States

#### Aquatic ecotoxicity

Product/ingredient name	Test	Result	Species	Exposure
naphtha	-	Acute EC50 3700 to 5100 ug/L Fresh water	Daphnia - Water flea - Daphnia pulex - LARVAE	48 hours
	-	Acute LC50 8.8 mg/L Fresh water	Fish - Rainbow trout, donaldson trout - Oncorhynchus mykiss - 2.6 g	96 hours
	-	Acute LC50 7.6 to 12 mg/L Fresh water	Crustaceans - Water flea - Simocephalus serrulatus - LARVAE	48 hours
	-	Acute LC50 3.7 to 4.2 mg/L Fresh water	Daphnia - Water flea - Daphnia pulex - LARVAE	48 hours
	-	Acute LC50 9.2 mg/L Fresh water	Fish - Bluegill - Lepomis macrochirus - 1 g	96 hours
	heptane	-	Acute LC50 4924000 ug/L Fresh water	Fish - Western mosquitofish - Gambusia affinis - Adult
-		Acute LC50 375000 ug/L Fresh water	Fish - Mozambique tilapia - Tilapia mossambica - 99 mm - 10 g	96 hours
methylcyclohexane	-	Acute LC50 180000 to 230000 ug/L Fresh water	Fish - Golden shiner - Notemigonus crysoleucas	96 hours
	-	Acute LC50 62000 to 80000 ug/L Fresh water	Fish - Golden shiner - Notemigonus crysoleucas	96 hours
	-	Acute LC50 55000 to 73000 ug/L Fresh water	Fish - Golden shiner - Notemigonus crysoleucas	96 hours
	-	Acute LC50 41000 to 65000 ug/L Fresh water	Fish - Golden shiner - Notemigonus crysoleucas	96 hours
	-			

## 12 . Ecological information

-	Acute LC50 5800 ug/L Marine water	Fish - Striped bass - Morone saxatilis - Juvenile (Fledgling, Hatchling, Weanling) - 9.2 cm - 8.5 g	96 hours
-	Acute LC50 235000 to 295000 ul/L Fresh water	Fish - Golden shiner - Notemigonus crysoleucas	96 hours

### Biodegradability

No known significant effects or critical hazards.

### Canada

#### Aquatic ecotoxicity

Product/ingredient name	Test	Result	Species	Exposure
naphtha	-	Acute EC50 3700 to 5100 ug/L Fresh water	Daphnia - Water flea - Daphnia pulex - LARVAE	48 hours
	-	Acute LC50 8.8 mg/L Fresh water	Fish - Rainbow trout,donaldson trout - Oncorhynchus mykiss - 2.6 g	96 hours
	-	Acute LC50 7.6 to 12 mg/L Fresh water	Crustaceans - Water flea - Simocephalus serrulatus - LARVAE	48 hours
	-	Acute LC50 3.7 to 4.2 mg/L Fresh water	Daphnia - Water flea - Daphnia pulex - LARVAE	48 hours
	-	Acute LC50 9.2 mg/L Fresh water	Fish - Bluegill - Lepomis macrochirus - 1 g	96 hours
heptane	-	Acute LC50 4924000 ug/L Fresh water	Fish - Western mosquitofish - Gambusia affinis - Adult	96 hours
	-	Acute LC50 375000 ug/L Fresh water	Fish - Mozambique tilapia - Tilapia mossambica - 99 mm - 10 g	96 hours
methylcyclohexane	-	Acute LC50 180000 to 230000 ug/L Fresh water	Fish - Golden shiner - Notemigonus crysoleucas	96 hours
	-	Acute LC50 62000 to 80000 ug/L Fresh water	Fish - Golden shiner - Notemigonus crysoleucas	96 hours
	-	Acute LC50 55000 to 73000 ug/L Fresh water	Fish - Golden shiner - Notemigonus crysoleucas	96 hours
	-	Acute LC50 41000 to 65000 ug/L Fresh water	Fish - Golden shiner - Notemigonus crysoleucas	96 hours
	-	Acute LC50 5800 ug/L Marine water	Fish - Striped bass - Morone saxatilis - Juvenile (Fledgling, Hatchling, Weanling) - 9.2 cm - 8.5 g	96 hours
	-	Acute LC50 235000 to 295000 ul/L Fresh water	Fish - Golden shiner - Notemigonus crysoleucas	96 hours

### Biodegradability

No known significant effects or critical hazards.

### Mexico

#### Aquatic ecotoxicity

Product/ingredient name	Test	Result	Species	Exposure
naphtha	-	Acute EC50 3700 to 5100 ug/L Fresh water	Daphnia - Water flea - Daphnia pulex - LARVAE	48 hours
	-	Acute LC50 8.8 mg/L Fresh water	Fish - Rainbow trout,donaldson trout - Oncorhynchus mykiss - 2.6 g	96 hours
	-	Acute LC50 7.6 to 12	Crustaceans - Water flea -	48 hours

## 12 . Ecological information

		mg/L Fresh water	Simocephalus serrulatus - LARVAE	
	-	Acute LC50 3.7 to 4.2 mg/L Fresh water	Daphnia - Water flea -	48 hours
	-	Acute LC50 9.2 mg/L Fresh water	Daphnia pulex - LARVAE	
heptane	-	Acute LC50 4924000 ug/L Fresh water	Fish - Bluegill - Lepomis macrochirus - 1 g	96 hours
	-	Acute LC50 4924000 ug/L Fresh water	Fish - Western mosquitofish - Gambusia affinis - Adult	96 hours
	-	Acute LC50 375000 ug/L Fresh water	Fish - Mozambique tilapia - Tilapia mossambica - 99 mm - 10 g	96 hours
methylcyclohexane	-	Acute LC50 180000 to 230000 ug/L Fresh water	Fish - Golden shiner - Notemigonus crysoleucas	96 hours
	-	Acute LC50 62000 to 80000 ug/L Fresh water	Fish - Golden shiner - Notemigonus crysoleucas	96 hours
	-	Acute LC50 55000 to 73000 ug/L Fresh water	Fish - Golden shiner - Notemigonus crysoleucas	96 hours
	-	Acute LC50 41000 to 65000 ug/L Fresh water	Fish - Golden shiner - Notemigonus crysoleucas	96 hours
	-	Acute LC50 5800 ug/L Marine water	Fish - Striped bass - Morone saxatilis - Juvenile (Fledgling, Hatchling, Weanling) - 9.2 cm - 8.5 g	96 hours
	-	Acute LC50 235000 to 295000 ug/L Fresh water	Fish - Golden shiner - Notemigonus crysoleucas	96 hours

### Biodegradability

No known significant effects or critical hazards.

**Other adverse effects** : No known significant effects or critical hazards.

## 13 . Disposal considerations

**Waste disposal** : The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

## 14 . Transport information

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
DOT Classification	1206	Consumer commodity	ORM-D	II		-
TDG Classification	1206	Heptanes	3	II		<b>Remarks</b> Limited quantity

## 14 . Transport information

<b>Mexico Classification</b>	1206	Heptanes	3	II		-
<b>ADR/RID Class</b>	1206	Heptanes	3	II		-
<b>IMDG Class</b>	1206	Heptanes. Marine pollutant (naphtha)	3	II		Marine pollutant <b>Remarks</b> Limited quantity
<b>IATA-DGR Class</b>	ID8000	Consumer commodity	9	II		-

PG\* : Packing group

## 15 . Regulatory information

### United States

#### HCS Classification

: Flammable liquid  
Irritating material  
Target organ effects

#### U.S. Federal regulations

: TSCA 4(a) final test rules: heptane  
TSCA 8(a) PAIR: heptane; methylcyclohexane  
**United States inventory (TSCA 8b):** All components are listed or exempted.  
TSCA 12(b) one-time export: heptane

**SARA 302/304/311/312 extremely hazardous substances:** No products were found.

**SARA 302/304 emergency planning and notification:** No products were found.

**SARA 302/304/311/312 hazardous chemicals:** heptane; methylcyclohexane; naphtha

**SARA 311/312 MSDS distribution - chemical inventory - hazard identification:**

heptane: Fire hazard; methylcyclohexane: Fire hazard, Immediate (acute) health hazard;  
naphtha: Fire hazard, Delayed (chronic) health hazard

#### DEA List I Chemicals (Precursor Chemicals)

: Not listed

#### DEA List II Chemicals (Essential Chemicals)

: Not listed

#### State regulations

: **Massachusetts Spill:** None of the components are listed.  
**Massachusetts Substances:** The following components are listed: NAPHTHA VM&P;  
HEPTANE (N-HEPTANE); METHYLCYCLOHEXANE  
**New Jersey Hazardous Substances:** The following components are listed: COAL TAR  
NAPHTHA; n-HEPTANE; METHYLCYCLOHEXANE  
**New Jersey Spill:** None of the components are listed.  
**New Jersey Toxic Catastrophe Prevention Act:** None of the components are listed.  
**Pennsylvania RTK Hazardous Substances:** The following components are listed:  
NAPHTHA; HEPTANE; CYCLOHEXANE, METHYL-

### Canada

#### WHMIS (Canada)

: Class B-2: Flammable liquid  
Class D-2B: Material causing other toxic effects (Toxic).

## 15 . Regulatory information


**Canadian lists** : **CEPA Toxic substances:** None of the components are listed.  
**Canadian ARET:** None of the components are listed.  
**Canadian NPRI:** The following components are listed: Naphtha; Heptane  
**Alberta Designated Substances:** None of the components are listed.  
**Ontario Designated Substances:** None of the components are listed.  
**Quebec Designated Substances:** None of the components are listed.

**Canada inventory** : All components are listed or exempted.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

### Mexico

**Classification** :



### International regulations

**International lists** : **Australia inventory (AICS):** All components are listed or exempted.  
**China inventory (IECSC):** All components are listed or exempted.  
**Japan inventory (ENCs):** Not determined.  
**Japan inventory (ISHL):** Not determined.  
**Korea inventory (KECI):** All components are listed or exempted.  
**New Zealand Inventory of Chemicals (NZIoC):** All components are listed or exempted.  
**Philippines inventory (PICCS):** All components are listed or exempted.

**Chemical Weapons Convention List Schedule I Chemicals** : Not listed

**Chemical Weapons Convention List Schedule II Chemicals** : Not listed

**Chemical Weapons Convention List Schedule III Chemicals** : Not listed

## 16 . Other information

**Label requirements** : EXTREMELY FLAMMABLE LIQUID AND VAPOR. FLAMMABLE. VAPOR MAY CAUSE FLASH FIRE. CAUSES EYE AND SKIN IRRITATION. MAY BE HARMFUL IF SWALLOWED. MAY CAUSE RESPIRATORY TRACT IRRITATION. PROLONGED OR REPEATED CONTACT MAY DRY SKIN AND CAUSE IRRITATION. CONTAINS MATERIAL THAT MAY CAUSE TARGET ORGAN DAMAGE.

**Hazardous Material Information System (U.S.A.)** :

Health	*	2
Flammability		3
Physical hazards		0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

## 16 . Other information

**Date of printing** : 1/27/2010.

**Date of issue** : 4/29/2009.

**Date of previous issue** : 4/23/2009.

**Version** : 1

✔ Indicates information that has changed from previously issued version.

### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.