

MATERIAL SAFETY DATA SHEET

MSDS Name: CONBOND C357 SOLVENT-FREE POSTFORMABLE ADHESIVE
MSDS Number: CB 357

MSDS Last Updated: MAR-22-2007 Printed On: 03/22/07
Page Number: 1

SECTION I - PRODUCT AND COMPANY INFORMATION

Product Name: CONBOND C357 SOLVENT-FREE POSTFORMABLE
ADHESIVE
CAS Number: MIXTURE
Hazard Rating: Health: 1 Fire: 0 Reactivity: 0 PPI: B

Company Identification: ITW TACC
AIR STATION INDUSTRIAL PARK
ROCKLAND MA 02370

Telephone/Fax: (781) 878-7015 (781) 871-6727
Chemtrec (24 Hour): (800) 424-9300

Trade Name: CONBOND C357 ADHESIVE
Product Code: C357
DOT Hazard Class
UN Number: NON REG
Shipping Name:
Packing Group:

CONBOND is a registered trademark of Illinois Tool Works, Inc.

SECTION II - HAZARDOUS INFORMATION

Ingredient Name	CAS Number	Percent	TSCA
-----------------	------------	---------	------

SECTION III - PHYSICAL DATA

Appearance/Color: CLEAR OR GREEN
Boiling Range: 212.°F
Evaporation Rate: Slower than n-Butyl Acetate
% Volatile Weight: 44.9%
% Volatile Volume: Not Available
Specific Gravity: 1.096
Weight/Volume Measure: 9.14
EPA Method 24 VOC: 0 g/L

MATERIAL SAFETY DATA SHEET

MSDS Name: CONBOND C357 SOLVENT-FREE POSTFORMABLE ADHESIVE
MSDS Number: CB 357

MSDS Last Updated: MAR-22-2007 Printed On: 03/22/07
Page Number: 2

Photo Chem Reactive Only VOC: 0.

SECTION IV - FIRE AND EXPLOSION HAZARD DANGER

Flammability Class: NA
Flash Range: Not Applicable
Explosive Range: Not Applicable

EXTINGUISHING MEDIA:

Water spray, carbon dioxide, dry chemical or foam.

SPECIAL FIREFIGHTING PROCEDURES:

After water evaporates, remaining material will burn. Breathing apparatus when fighting fires in enclosed areas.

UNUSUAL FIRE & EXPLOSION HAZARDS:

Decomposition products may cause a health hazard.

SECTION V - HEALTH HAZARD DATA

PERMISSIBLE EXPOSURE LEVEL:

SEE SECTION VIII.

EFFECTS OF OVEREXPOSURE:

INHALATION: Materials are low in volatility and therefore not likely to pose a problem.

EYES: May cause minor irritation.

SKIN: Not likely to be absorbed in toxic amounts. Avoid skin contact as much as possible; upon repeated contact, slight skin irritation may occur.

INGESTION: None reported, not likely route of entry.

FIRST AID:

INHALATION: Get fresh air.

EYES: Flush with water for at least 15 minutes.

SKIN: Wash with mild soap and water; apply a mild cream.

INGESTION: Small amounts are not expected to produce adverse health effects. Larger amounts should be recovered by aspiration. Call a physician.

SECTION VI - REACTIVITY DATA

Stability: This product is stable

MATERIAL SAFETY DATA SHEET

MSDS Name: CONBOND C357 SOLVENT-FREE POSTFORMABLE ADHESIVE
MSDS Number: CB 357

MSDS Last Updated: MAR-22-2007 Printed On: 03/22/07
Page Number: 3

Hazardous Polymerization: Hazardous polymerization will not occur

INCOMPATIBILITY:

Strong acids or alkaline materials.

CONDITIONS TO AVOID:

None known.

HAZARDOUS DECOMPOSITION PRODUCTS:

Fumes, smoke, carbon monoxide, carbon dioxide in the case of incomplete combustion.

===== **SECTION VII - SPILL OR LEAK PROCEDURES** =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Confine to small area. Use absorbent to clean up. Place in container for disposal.

WASTE DISPOSAL METHOD:

Dispose in accordance with federal, state and local regulations.

===== **SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION** =====

Occupational Exposure Limits:

ACGIH TLV	ACGIH TLV-C	ACGIH STEL	OSHA STEL	OSHA PEL
-----------	-------------	------------	-----------	----------

RESPIRATORY PROTECTION:

None required for normal use.

VENTILATION:

Natural ventilation should be adequate under normal conditions.

PROTECTIVE GLOVES:

Impervious gloves, if needed, to avoid repeated or prolonged skin contact.

EYE PROTECTION:

Safety glasses. Face shield as necessary if spraying.

OTHER PROTECTIVE EQUIPMENT:

Not likely to be needed.

===== **SECTION IX - SPECIAL PRECAUTIONS** =====

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

Do not store above 125 degrees F or below freezing or damage may occur to product.

OTHER PRECAUTIONS:

MATERIAL SAFETY DATA SHEET

MSDS Name: CONBOND C357 SOLVENT-FREE POSTFORMABLE ADHESIVE
MSDS Number: CB 357

MSDS Last Updated: MAR-22-2007 Printed On: 03/22/07
Page Number: 4

For professional or industrial use only. Follow label instructions. Keep out of the reach of children. Not for consumption. No smoking. Do not breathe fumes. Avoid contact with body. Turn off all pilot lights, flames, stoves, heaters, electric motors, welding equipment and other sources of ignition. Close all containers when not in use. Empty containers must not be washed and re-used for any purpose. Contact lens wearers take appropriate precautions. Wash hands thoroughly after handling.

For spray applications, use only with approved spray equipment.

For flammable products, vapors may cause flash fire or ignite explosively. To prevent buildup of vapors, use adequate ventilation (e.g. open all windows and doors to achieve cross-ventilation). Containers may be hazardous when empty. Never use welding or cutting torch on or near container.

=====
SECTION X - ADDITIONAL REGULATORY INFORMATION
=====

None.

=====
DISCLAIMER
=====

***** NOTICE *****

This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of ITW TACC. The data on this sheet relates only to the specific material designated herein. ITW TACC assumes no legal responsibility for use or reliance upon these data.
