

M.L. Campbell 224 Catherine Street Fort Erie, Ontario L2A 5M9 Canada

Tel: 1(800) 364-1359 Web: <u>www.mlcampbell.com</u>

Product Information (PI) Sheet

Product: Spray Zits - Aerosol Lacquer Spray Cans

Code(s): WZ-1 Lacquer Sanding Sealer

WZ-2 Clear Satin Lacquer WZ-3 Clear Gloss Lacquer

WZ-4 Shading Lacquer Medium Toner WZ-5 Shading Lacquer Dark Toner

Description: These are 12 ounce AVDP aerosol spray cans of clear lacquer finishes and shading

lacquer toners. They are fast, easy, and convenient to use with no application equipment required. The two toner colors are specially formulated to cover some of

your requirements for touch-up and furniture repair colors.

Uses: Spray Zit aerosol products are designed for touch-up, furniture repair, shading and

highlighting of stain colors, as well as finishing of small objects or areas such as

exposed wood on upholstered furniture.

Physical Properties (packaged)				
Coverage: Clear finishes: 25-30 sq .ft per 12 oz can				
	Shading Lacquers: 40-45 sq. ft. per 12 oz. can			
Flash Point (PMCC):	-25°F or -31.6°C			
Sheen (60° Glossmeter):	WZ-2 Satin – 20, WZ-3 Gloss - 90			

Surface Preparation

Apply over smooth sanded wood, free of any contaminants, polish or finish residue. May be applied over bare wood, clear or lacquer stain/finishes.

Application Procedure

Before use: Shake can vigorously for 3 minutes after agitation ball inside becomes audible. Hold Spray can 10 to 12 inches from work. Spray short, light passes, holding nozzle perpendicular to work. Release spray nozzle trigger after each pass.

After use: Invert spray can, trigger nozzle for short bursts until all finish is cleared from spray head, and only gas is being propelled.

Shading-Blending toners: Touch up on furniture repair. Use medium toner for popular shades of walnut, or medium maple colors containing a reddish cast or background. Use dark toner for colors of a yellow cast. Color depth, from light to very dark, is controlled by the amount of color or spray passes applied.

Clear Finishes: Apply 4 to 5 light passes for one coat build. The passes are to be applied simultaneously. If additional build is required, let air dry 30 minutes and apply another 4 or 5 passes.

Packaging/Shipping				
Available Units:	6 cans per carton.	Shipping weight 7 lbs. per carton		

Storage

- Do not store above 120°F or 48.9°C.
- Contents under pressure.
- Protect from heat or open flame.

DOT Classification					
Flammable Liquid	Red Label	UN1263			

B/L Description						
Paint	UN 1263	3	Pg II			

Caution

- THESE PRODUCTS ARE DESIGNED FOR SHOP APPLICATION AND PROFESSIONAL USE ONLY.
- Use only after all safety information is understood.
- Refer to the Material Safety Data Sheet (MSDS) for additional information.

Testing

Due to the wide variety of substrates, surface preparation methods, application methods, and environments, customers should test the complete system for adhesion and compatibility under their conditions prior to full-scale application.

Notes

The information, rating, and options stated here pertain to the material currently offered and represent the results of tests believed to be reliable. However, due to variations in customer handling and methods of application that are not known or under our control, M.L. Campbell cannot make any warranties as to the end result. *Thank you for using M.L. Campbell Wood Finishing products*.